Hybrid Kablolar / Hybrid Cables





Yapı / *Construction*

Kontrol Damarları
İletken : Elektrolitik Tavlı Bakır (Klass 5)
İzolasyon : Köpüklü PE
İzolasyon Rengi : Mavi, Kırmızı
1. Ekran : AL-PES Bant + Kalaylı Bükülü Bakır Toprak Teli
2. Ekran : Kalaylı Bakır Örgü
Kılıf : PVC
Kılıf Rengi : Siyah

Enerji Damarları
İletken : Elektrolitik Tavlı Bakır (Klass 5)
İzolasyon : PVC
İzolasyon Rengi : Kahve, Siyah, Sarı-Yeşil

Kablo Dizaynı
Büküm : Kılıflı Kontrol Damarları Enerji Damarları ile Birlikte
Genel Ekran : Tele Bant
Dış Kılıf : Esnek PVC Mat
Dış Kılıf Rengi : Siyah

Control Cores
Conductor : Electrolytic Stranded Annealed Copper (Cl. 5),
Insulation : Foam PE
Insulation Colour : Blue, Red
1. Screen : AL-PES Tape + Tinned Copper Drain Wire
2. Screen : Tinned Copper Braiding
Sheath : PVC
Sheath Colour : Black

Power Cores
Conductor : Electrolytic Stranded Annealed Copper (Cl. 5),
Insulation : PVC
Insulation Colour : Brown, Black, Yellow-Green

Cable Desing
Stranding : Sheathed Control Cores With Together Power Cores
Overall Screen : Tele Tape
Outer Sheath : Flexible PVC Matt
Outer Sheath Colour : Black

Kullanıldığı Yerler / *Applications*

Bu kablolar dijital ses dolapları ve güç bağlantısı sırasında aydınlatma kontrolü için kullanılır.

This Cable used for digital audio cabinets and lighting control when power connection.

Teknik Bilgiler / *Technical Data*

İletken Direnci *Conductor Resistance*		**Yalıtkan Direnci** *Insulation Resistance*		**Kapasite** *Capacitance*	**Empedans** *Impedance*	**Çalışma Sıcaklığı** *Temperature Range*	**Bükülme Yarıçapı** *Bending Radius*
mm²	Ω/km	MΩxKm		pF/m	µH/m	°C	
0,22	86	Control Cores 5000	Power Cores 200	80	0,56	-30°C ...+70°C	12XD
1,50	13,30				0,56		
2,50	7,98				0,50		

Malzeme Kodu *Products Code*	**Kesit** *Cross Section* (mm²)	**Dış Çap** *Outer Diameter* (mm~)	**Toplam Ağırlık** *Total Weight* (kg/km~)
8003407035	2x0,22+3x1,50mm²	10,55	158
8003408035	2x0,22+3x2,50mm²	11,00	185